

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-500

Version 1.0 GB / EN Revision Date: 17.07.2019 Date of last issue: -  
Date of first issue: 17.07.2019

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Carsystem KS-500

Product code : 126.034

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Solvent-borne coatings, Corrosion inhibitor

Recommended restrictions on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH  
Esinger Steinweg 50  
25436 Uetersen  
Germany  
info@vosschemie.de

Telephone : 04122 717 0  
Telefax : 04122 717158

**Responsible Department** : Laboratory  
  
04122 717 0  
sds@vosschemie.de

#### 1.4 Emergency telephone number

Telephone : AU POISON INFORMATION CENTRE  
13 11 26

Importer : Sydney Automotive Paints and  
Equipment Pty Ltd.  
Unit A4, 366 Edgar Street, Condell Park  
NSW 2200 Australia  
Ph: 02 9772 9000  
Email: reception@sape.com.au

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-500

Version	Revision Date:	Date of last issue: -
1.0 GB / EN	17.07.2019	Date of first issue: 17.07.2019

---

### SECTION 2: Hazards identification


#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe the mist or vapours. P273 Avoid release to the environment. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. <b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. <b>Disposal:</b>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-500

Version 1.0 GB / EN Revision Date: 17.07.2019 Date of last issue: -  
Date of first issue: 17.07.2019

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous components which must be listed on the label:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Solvent naphtha (petroleum), light arom.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Mixture

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	1174921-73-3 927-241-2 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20
Solvent naphtha (petroleum), light arom.	64742-95-6 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 10 - < 20
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1 919-446-0 01-2119458049-33	Flam. Liq. 3; H226 STOT SE 3; H336 STOT RE 1; H372 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2.5 - < 10
propylene carbonate	108-32-7 203-572-1 607-194-00-1 01-2119537232-48	Eye Irrit. 2; H319	>= 1 - < 10

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-500

Version 1.0 GB / EN Revision Date: 17.07.2019 Date of last issue: -  
Date of first issue: 17.07.2019

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
Move out of dangerous area.  
Take off contaminated clothing and shoes immediately.  
Do not leave the victim unattended.  
Symptoms of poisoning may appear several hours later.  
Show this safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
If easy to do, remove contact lens, if worn.  
Consult a physician.
- If swallowed : Do NOT induce vomiting.  
Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

### SECTION 5: Firefighting measures

**Hazchem: +3Y**

#### 5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Water spray jet  
Alcohol-resistant foam
- Unsuitable extinguishing : High volume water jet

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-500

Version	Revision Date:	Date of last issue: -
1.0 GB / EN	17.07.2019	Date of first issue: 17.07.2019

---

media

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
- Hazardous combustion products : Hazardous decomposition products due to incomplete combustion  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation, especially in confined areas.  
Remove all sources of ignition.  
Do not smoke.  
Avoid contact with skin, eyes and clothing.  
In the case of vapour formation use a respirator with an approved filter.

### 6.2 Environmental precautions

- Environmental precautions : Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.  
Do not flush with water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-500

Version 1.0 GB / EN Revision Date: 17.07.2019 Date of last issue: -  
Date of first issue: 17.07.2019

### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Wear personal protective equipment.

Use only in well-ventilated areas.

Advice on protection against fire and explosion : Vapours may form explosive mixtures with air.  
Keep away from open flames, hot surfaces and sources of ignition.  
Do not smoke.  
Take measures to prevent the build up of electrostatic charge.  
Use explosion-proof equipment.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container.  
Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition.  
Protect from moisture.  
Keep away from direct sunlight.

Advice on common storage : Keep away from food and drink.

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m3
	Workers	Skin contact	Long-term systemic effects	77 mg/kg
	Consumers	Inhalation	Long-term systemic effects	185 mg/m3
	Consumers	Skin contact,	Long-term systemic	46 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-500

Version 1.0 GB / EN Revision Date: 17.07.2019 Date of last issue: -  
Date of first issue: 17.07.2019

		Oral	effects	
--	--	------	---------	--

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

#### Hand protection

Material : Nitrile rubber

Break through time : > 480 min

Glove thickness :  $\geq 0.12$  mm

Directive : DIN EN 374

Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.  
The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.  
The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.  
Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.  
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Organic vapour type (A)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
Avoid contact with the skin and the eyes.  
Use only with adequate ventilation.

#### Environmental exposure controls

Soil : Avoid subsoil penetration.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-500

Version	Revision Date:	Date of last issue: -
1.0	17.07.2019	Date of first issue: 17.07.2019

---

Appearance	: liquid
Colour	: black
Odour	: characteristic
pH	: not determined
Melting point/freezing point	: not determined
Initial boiling point and boiling range	: 135 °C
Flash point	: 29 °C
Upper explosion limit / Upper flammability limit	: 6 %(V)
Lower explosion limit / Lower flammability limit	: 0.8 %(V)
Vapour pressure	: 5 hPa (20 °C) 30 hPa (50 °C)
Density	: 1.03 g/cm <sup>3</sup> (20 °C)
Solubility(ies) Water solubility	: immiscible
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: > 200 °C
Viscosity Viscosity, dynamic	: 3,500 mPa.s (20 °C)
Viscosity, kinematic	: not determined
Explosive properties	: Not explosive In use, may form flammable/explosive vapour-air mixture.

### 9.2 Other information

Self-ignition : not auto-flammable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if used as directed.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-500

Version	Revision Date:	Date of last issue: -
1.0 GB / EN	17.07.2019	Date of first issue: 17.07.2019

---

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : None known.

### 10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Acute oral toxicity : LD50 Oral (Rat): > 15,000 mg/kg  
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat): > 4.951 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402

#### **Solvent naphtha (petroleum), light arom.:**

Acute oral toxicity : LD50 Oral (Rat, female): ca. 3,492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.193 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 3,160 mg/kg  
Method: OECD Test Guideline 402

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-500

Version 1.0 GB / EN Revision Date: 17.07.2019 Date of last issue: -  
Date of first issue: 17.07.2019

---

### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

- Acute oral toxicity : LD50 Oral (Rat): > 15,000 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 13.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 Dermal (Rat): ca. 3,400 mg/kg

### propylene carbonate:

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402

### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

### Components:

#### Solvent naphtha (petroleum), light arom.:

Result : Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Solvent naphtha (petroleum), light arom.:

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-500

Version 1.0 GB / EN Revision Date: 17.07.2019 Date of last issue: -  
Date of first issue: 17.07.2019

---

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Solvent naphtha (petroleum), light arom.:**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Assessment : May cause drowsiness or dizziness.

#### **Solvent naphtha (petroleum), light arom.:**

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Assessment : May cause drowsiness or dizziness.

### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### **Components:**

#### **Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Target Organs : Central nervous system  
Assessment : Causes damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

May be fatal if swallowed and enters airways.

#### **Solvent naphtha (petroleum), light arom.:**

May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-500

Version 1.0 GB / EN Revision Date: 17.07.2019 Date of last issue: -  
Date of first issue: 17.07.2019

---

### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

May be fatal if swallowed and enters airways.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - < 30 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 22 - < 46 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR: 0.182 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0.317 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

#### **Ecotoxicology Assessment**

- Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

#### **Solvent naphtha (petroleum), light arom.:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3.2 mg/l  
End point: Immobilization  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR: 1.228 mg/l  
Exposure time: 28 d

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-500

Version 1.0 GB / EN Revision Date: 17.07.2019 Date of last issue: -  
Date of first issue: 17.07.2019

---

Species: *Oncorhynchus mykiss* (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 2.144 mg/l  
Exposure time: 21 d  
Species: *Daphnia magna* (Water flea)

### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Toxicity to fish : LL50 (*Oncorhynchus mykiss* (rainbow trout)): 10 - 30 mg/l  
End point: mortality  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (*Daphnia magna* (Water flea)): 10 - 22 mg/l  
End point: Immobilization  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (*Pseudokirchneriella subcapitata* (green algae)): 4.1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 0.13 mg/l  
Exposure time: 28 d  
Species: *Oncorhynchus mykiss* (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0.28 mg/l  
Exposure time: 21 d  
Species: *Daphnia magna* (Water flea)  
Method: OECD Test Guideline 211

### propylene carbonate:

Toxicity to fish : LC50 (*Cyprinus carpio* (Carp)): > 1,000 mg/l  
Exposure time: 96 h  
Method: Regulation (EC) No. 440/2008, Annex, C.1

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 1,000 mg/l  
Exposure time: 48 h  
Method: Regulation (EC) No. 440/2008, Annex, C.2

Toxicity to algae : EC50 (*Desmodesmus subspicatus* (green algae)): > 900 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

## 12.2 Persistence and degradability

### Components:

#### Solvent naphtha (petroleum), light arom.:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-500

Version	Revision Date:	Date of last issue: -
1.0 GB / EN	17.07.2019	Date of first issue: 17.07.2019

---

Method: OECD Test Guideline 301F

### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Biodegradability : Biodegradation: 75 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

### 12.3 Bioaccumulative potential

#### Components:

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Partition coefficient: n-octanol/water : No data available

#### propylene carbonate:

Partition coefficient: n-octanol/water : log Pow: -0.48 (20 °C)

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
Dispose of in accordance with local regulations.  
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of in accordance with local regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-500

Version 1.0 GB / EN Revision Date: 17.07.2019 Date of last issue: -  
Date of first issue: 17.07.2019

---

Waste Code : The following Waste Codes are only suggestions:  
08 01 11, waste paint and varnish containing organic solvents  
or other hazardous substances

---

### SECTION 14: Transport information

#### 14.1 UN number

ADN : UN 1139  
ADR : UN 1139  
RID : UN 1139  
IMDG : UN 1139  
IATA : UN 1139

#### 14.2 UN proper shipping name

ADN : COATING SOLUTION  
(Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2%  
aromatics, PETROLEUM DISTILLATES, N.O.S.)  
ADR : COATING SOLUTION  
(Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2%  
aromatics, PETROLEUM DISTILLATES, N.O.S.)  
RID : COATING SOLUTION  
(Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2%  
aromatics, PETROLEUM DISTILLATES, N.O.S.)  
IMDG : COATING SOLUTION  
(Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2%  
aromatics, PETROLEUM DISTILLATES, N.O.S.)  
IATA : Coating solution  
(Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2%  
aromatics, PETROLEUM DISTILLATES, N.O.S.)

#### 14.3 Transport hazard class(es)

ADN : 3  
ADR : 3  
RID : 3  
IMDG : 3  
IATA : 3

#### 14.4 Packing group

ADN  
Packing group : III  
Classification Code : F1  
Labels : 3  
ADR

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-500

Version	Revision Date:	Date of last issue: -
1.0 GB / EN	17.07.2019	Date of first issue: 17.07.2019

Packing group : III  
Classification Code : F1  
Labels : 3  
Tunnel restriction code : (E)

### RID

Packing group : III  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

### IMDG

Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

### IATA (Cargo)

Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

*Hazchem: •3Y*

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High : Not applicable



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**VOSSCHEMIE**

## Carsystem KS-500

Version	Revision Date:	Date of last issue: -
1.0	GB / EN 17.07.2019	Date of first issue: 17.07.2019

---

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
P5c FLAMMABLE LIQUIDS

### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

---

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H372	: Causes damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regula-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

VOSSCHEMIE

## Carsystem KS-500

Version	Revision Date:	Date of last issue: -
1.0 GB / EN	17.07.2019	Date of first issue: 17.07.2019

tion; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336
STOT RE 2	H373
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.